

HANDI - BIND™

Document integrity is maintained with this simple, accurate and extra strong document-binding machine.

• Fast:	Only 30 seconds are needed from drilling to binding. This means that less time is lost collating documents and records by hand.
• Dual Function:	Although designed as a document-binding machine, the HANDI-BIND™ can also be used as a paper drill only.
• Versatile:	Important office papers, documents and records can now be bound into sturdy volumes for permanent keeping and instant reference. Librarians find the HANDI-BIND™ useful for: <ul style="list-style-type: none"> • On-site binding for current periodical” maintenance. • Temporary binding for volumes with missing issues. • Temporary binding for volumes to be filmed later • Binding many flimsy sheets such as newsletter type items and loose office documents. • Computer printouts.
• Self-Adjusting:	If its paper, any size will do, even formats used in drawings and blueprints. Maximum bulk is 2” [50-mm]. Thickness adjustment is not necessary.
• Extra Strong:	Bound documents are extremely durable. Molding a plastic tube under heat and pressure performs the binding. So strong is the binding that pages never fall out.
• Simple & Effortless:	Just press the START button. Drilling and binding is thereafter fully automatic until the document is bound.
• User-Friendly:	The HANDI-BIND™ notifies you when it is out of tube, or when the drill is dull or in the event of a malfunction. An indicator on the illustrated operation panel lights up to help quickly identify the point.
• Heavy Duty Reliable & Quiet:	The HANDI-BIND™ is ruggedly designed and built for heavy industrial use and trouble-free maintenance to give many years of reliable service.



Technical Data

Binding capacity:	1/32 – 2 inches thickness [1-50 mm]
Binding Speed:	50 Hz: Approx. 29 sec; 60 Hz: Approx. 27.5 sec
Drive system:	100W, 23W, 14W condenser motors (x3) 2.5W synchronous motor

Heating system:	240V/150W or 120V/120W heaters (x2)
Binding method:	Plastic tube heat compression molding
Power supply:	110/115, 220/240V, 50/60Hz
Power consumption:	Max. 700W Min. 10W
Physical:	Height 26” [662] Width 17-1/2” [440] Depth 17-1/2” [440]
Weight:	84 lbs. [38 kg.]

Note: Technical data subject to change.

MEKATRONICS, INC./BENDROR INTERNATIONAL, LTD.

85 Channel Drive, Port Washington, NY 11050 • Telephone: (516) 883-6805 • FAX: (516) 883-6948